



# Sanitary Mixer FRESH

Sink Mixer

Datasheet  
00135  
00136



00135



00136

Model	Colour	Contents of package
00135	Chrome	Ball valve
00136	Chrome	/

**Contents and colour**

Body: brass acc. EN 12164, chrom plated  
 Cartridge: 40 mm  
 Handle: brass, chrom plated  
 Sealing elements: rubber EPDM  
 Option: spout rotates around its horizontal axis.

**Construction**

Connections:	Flexible connecting hose for domestic tap fittings G3/8x450
Recommendable pressure:	Working pressure: up to 3 - 5 bar
Maximum pressure:	Working pressure: up to 8 bar
Minimum pressure:	Working pressure: up to 0,5 bar
Recommendable temp.:	Working temperature: 5 - 65°C
Maximum temperature:	Working temperature: 80°C

**Specification**

You have to wash out all pipes before assembling.

Connect sanitary mixer and primary water pipe with flexible hose. Remove aerator and rotate mixer handle in totally open position. Slowly open pipe valves and manipulate with mixer handle in all positions.

Repairment of the mixer must be always performed by a qualified person. After assembling, we advice to wash out mixer for one hour.

We recommend to reduce water pressure over 5 bar with suitable pressure reducer.

**Instruction for assembling and maintenance**