


Sanitary Mixer FRESH

Shower / Bath Mixer


Datasheet

00335

00435



00335



00435

Model	Colour	Contents of package
00335	Chrome	Hand shover and sliding rail, hose
00435	Chrome	Hand shover and sliding rail, hose

Contents and colour

Body: brass acc. EN 12164, chrom plated
 Cartridge: 35 mm
 Handle: brass, chrom plated
 Sealing elements: rubber EPDM
 Brass spout L=100 mm
 Automatic diverter Neoperl
 Flexible double interlock stainless steel hose L=1500 mm
 Hand shover and sliding rail

Construction

Connections:	Flexible connecting hose for domestic tap fittings G3/8x450
Recommendable pressure:	Working pressure: up to 3 - 5 bar
Maximum pressure:	Working pressure: up to 8 bar
Minimum pressure:	Working pressure: up to 0,5 bar
Recommendable temp.:	Working temperature: 5 - 65°C
Maximum temperature:	Working temperature: 80°C

Specification

Sanitary Mixer FRESH

Basin Mixer

Datasheet

00035 00040
00038 01035
00039

You have to wash out all pipes before assembling.

Connect sanitary mixer and primary water pipe with flexible hose. Remove aerator and rotate mixer handle in totally open position. Slowly open pipe valves and manipulate with mixer handle in all positions.

Repairment of the mixer must be always performed by a qualified person. After assembling, we advice to wash out mixer for one hour.

We recommend to reduce water pressure over 5 bar with suitable pressure reducer.

**Instruction for
assembling
and maintenance**